



Performance Curves

LKH-/ LKHP-/ LKHI-45, 50 Hz

Motor: **3000 rpm. synchr.**
 Tolerance: $\pm 5\%$.
 Impeller, Max. dia.: 178 mm
 Impeller, Min. dia.: 140 mm
 Pump inlet, Dia.: 101.6 mm, DN 100
 Pump outlet, Dia.: 76 mm, DN 80



Performance data refer to water at 20°C.

NOTE!

The curves refer to motor: 15 kW, 2930 rpm. asynchr., 50 Hz.

For smaller motors, reduce head (H) with: 3%.

DO NOT FORGET THE SAFETY FACTOR.





Motor: **1500 rpm. synchr.**
 Tolerance: $\pm 5\%$.
 Impeller, Max. dia.: 178 mm
 Impeller, Min. dia.: 140 mm
 Pump inlet, Dia.: 101.6 mm, DN 100
 Pump outlet, Dia.: 76 mm, DN 80

Performance data refer to water at 20°C.

NOTE!

The curves refer to motor: 2.2 kW, 1430 rpm. asynchr., 50 Hz.

DO NOT FORGET THE SAFETY FACTOR.



The information contained herein is correct at the time of issue, but may be subject to change without prior notice.

How to contact Alfa Laval

Contact details for all countries are continually updated on our website. Please visit www.alfalaval.com to access the information direct.